

Pittsburg County, Oklahoma  
**COUNTY PURCHASING OFFICE**  
 Pittsburg County Court House  
 McAlester, Oklahoma  
 Phone: (918) 423-4934

**INVITATION TO BID**

PLEASE REVIEW TERMS AND CONDITIONS ON REVERSE SIDE RELATING TO SUBMISSION OF THIS BID.

Notarized Affidavit completions and signature required on reverse side.

DATE ISSUED	<b>8-Jan-18</b>
PAGE 1 OF _____	

BID NUMBER <b>BID # 19</b>	BID CLOSING DATE AND HOUR <b>January 19, 2018 @ 5:00PM</b>	REQUIRED DELIVERY DATE <small>Days after award of Purchase Order</small>
-------------------------------	---	---

TERMS:	DATE OF DELIVERY:
--------	-------------------

Item	Quantity	Unit of issue	DESCRIPTION	Unit Price	Total
			<p><b>Board of County Commissioners wishes to advertise for the following for Indianola Volunteer Fire Department:</b></p> <p><b>One (1) 70 Gallon Poly Skid Unit</b></p> <p><b>See Specifications Attached</b></p> <p><b><u>PLEASE MARK CLEARLY ON FRONT OF SHIPPING ENVELOPE BID &amp; BID NUMBER</u></b></p>		

**TERMS AND CONDITIONS**

1. Sealed bids will be opened in the Commissioner's Conference Room, Pittsburg County Courthouse, McAlester, Oklahoma, at the time and date shown on the invitation to bid form.
2. Late bids will not be considered. Bids must be received in sealed envelopes (one to an envelope) with bid number and closing date written on the outside of the envelope.
3. Unit prices will be guaranteed correct by the bidder.
4. Firm prices will be F.O.B. destination.
5. Purchases by Pittsburg County, Oklahoma, are not subject to state or federal taxes.
6. This bid is submitted as a legal offer and any bid when accepted by the County constitutes a firm contract.
7. Oklahoma laws require each bidder submitting a bid to a county for goods or services to furnish a notarized sworn statement of non-collusion. A form is supplied below.
8. Bids will be firm until delivered.

(DATE)

AFFIDAVIT: I, the undersigned, of lawful age, being first duly sworn on oath say that he (she) is the agent authorized by the bidder to submit the above bid. Affiant further states that the bidder has not been a party to any collusion among bidders in restraint of freedom of competition by agreement to bid at a fixed price or to refrain from bidding; or with any state official or employee as to quantity; quality or price in the prospective contract or any other terms of said prospective contract; or in any discussions between bidders and any state official concerning exchange of money or other thing of value for special consideration in the letting of a contract; that the bidder/contractor has not paid, given or donated or agreed to pay, give or donate to any officer or employee of the State of Oklahoma (or other entity) any money or other thing of value, either directly or indirectly in the procuring of the award of a contract pursuant to this bid.

Subscribed and sworn before this \_\_\_\_\_ day  
of \_\_\_\_\_ 20\_\_\_\_\_ (seal)

My commission expires \_\_\_\_\_ Signed by: \_\_\_\_\_ Title: \_\_\_\_\_  
(MANUAL SIGNATURE OF UNDERSIGNED)

\_\_\_\_\_  
NOTARY PUBLIC (CLERK OR JUDGE)  
Address: \_\_\_\_\_ Phone: \_\_\_\_\_  
City: \_\_\_\_\_ State \_\_\_\_\_  
Zip \_\_\_\_\_

NOTE: Other terms and conditions can be added at the discretion of the county officers.

RESOLUTION 18-150

To  
Advertise

The Board of County Commissioners, Pittsburg County, met in regular session on Monday, January 8, 2018.

WHEREAS, the Board of County Commissioners wishes to advertise for the following for Indianola Volunteer Fire Department:

One (1) 70 Gallon Poly Skid Unit

A bid package containing complete specifications and an "Invitation to Bid" are available at the Pittsburg County Clerk's Office, 115 E. Carl Albert Parkway, Room 103, McAlester, Oklahoma 74501 or online at [pittsburg.okcounties.org](http://pittsburg.okcounties.org).

THEREFORE, each competitive bid submitted to the County must be accompanied with an affidavit for filing with the competitive bid form, as required by 61 O.S. § 138.

Sealed bids will be received and filed with the Pittsburg County Clerk until Friday, January 19, 2018 at 5:00 p.m. All bids received after 5:00 p.m. on January 19, 2018 will NOT BE OPENED. Bids will be opened on Monday, January 22, 2018 at 10:00 a.m. in the Board of County Commissioners Conference Room, 115 E. Carl Albert Parkway, McAlester, Oklahoma. Bid will be awarded to the lowest or best bidder. The Board of County Commissioners, Pittsburg County, reserves the right to reject any and all bids at re-advertise.

BOARD OF COUNTY COMMISSIONERS  
PITTSBURG COUNTY, OKLAHOMA

ATTEST:



CHAIRMAN

*Ron Selau*

MEMBER

*Chub Ryan*

MEMBER

*[Signature]*

COUNTY CLERK

*Hope Trammell*

# Indiana Volunteer Fire Dept.

## 70 GALLON POLY SKID UNIT SPECIFICATION

**TANK:** 70 GALLON POLY, ON A POLY SKID 54" X 38" (FIT ATV BED ) with fill tower and sight glass for water level viewing

**PUMP:** The pump shall be a direct mount 2-stage self-priming centrifugal pump with the pump body, diffusers, discharge manifold, and intake flange made of a high quality corrosive resistant aluminum. The impeller and wear rings shall be made of a reinforced non-corrosive glass fiber nylon composite material to prevent galvanic corrosion from taking place between pump components – **NO EXCEPTIONS.**

The impellers shall be 6.28 inches in diameter with anti-rotation flats as an integral part of the impeller hub.

The pump shaft shall be a hexagonal engine drive shaft extension through which the mechanical rotary seal mounts preventing the pump media from coming in contact with and/or corroding the engine drive shaft. In addition, the pump seal shall be a maintenance free mechanical rotary seal, shall be externally pressurized, and shall incorporate a blister-resistant carbon seal face with a ceramic seat. – **NO EXCEPTIONS.**

A 2" BSP priming port shall be located on the top side of the pump discharge manifold and be sealed through the means of a hard anodized aluminum removable cap.

The pump body, discharge manifold, and pump intake flange shall be finished with an extremely durable red powder coat.

**Engine:** The engine shall be a manual (recoil) start 4-stroke Honda horizontal drive GX270 series OHV air cooled gasoline engine **OR EQUIVALENT.** The engine net horsepower shall be 8.5 HP at 3,600 RPM with a net torque of 14.1 lb-ft at 2,500 rpm. The engine shall have a 3.03 bore, 2.28 inches of stroke, and a displacement of 16.48 cubic inches. The engine shall meet current EPA and CARB emission standards. The engine shall have the option of utilizing the engines 12VDC electric start system. The option shall have a 1 amp regulating alternator and be pre-wired with a 3 feet engine harness to allow it to connect to a mating control harness via an 8-pin industrial sealed quick-connect connector – **NO EXCEPTIONS.**

**Muffler:** The muffler shall be a canister type with an approved forestry spark arrestor.

**Fuel Tank:** The unit shall have a fuel tank with a manual shut off valve that is an integral part of the pump/engine unit and meet current EPA evaporative emission standards. The integral fuel tank shall have a 5.6 quart fuel capacity.

**Pump Suction/Discharge Ports:** The pump intake shall be a 2" male NPT pipe thread and be an integral part of the pump intake flange.

The pump shall have a manifold discharge consisting of two 1 inch male NPT ports each located on opposite sides of the manifold and a 1.5 inch male NPT port located above and parallel to the pump intake port.

The pump intake and discharge shall be in locations where applicable hose thread adapters can be installed without interference.

**VALVES:** Manifold will consist of 3-1-inch stainless steel valves and 1-1.5" stainless steel valve on the discharge side of the pump. There will be a 2" stainless steel valve located on the suction side of the pump between the tank and suction inlet. The suction side of the pump shall be equipped with such fittings necessary to preform drafting functions.

**REEL:** Hanney electric rewind EF1520-17-18RT w/ ASSB C guides **OR EQUIVALENT**

**HOSE:** 200 ft. of ½" high pressure style hose with ½" male NPT thread on one end and quick connect coupling on the nozzle end.

**NOZZLE:** Dual action spray wand style w/ quick connect and brackets mounted to the skid unit.

**BATTERY:** 12 VOLT AUTO STYLE BATTERY IN CASE

All discharges to have a chrome cap or plug

**THIS UNIT WILL BE SELF-CONTAINED; THERE WILL BE NO ADDITIONAL WIRING OR FUEL LINES NEEDED.**