

Pittsburg County, Oklahoma
COUNTY PURCHASING OFFICE
 Pittsburg County Court House
 McAlester, Oklahoma
 Phone: (918) 423-4934

INVITATION TO BID

PLEASE REVIEW TERMS AND CONDITIONS ON REVERSE
 SIDE RELATING TO SUBMISSION OF THIS BID.

Notarized Affidavit completions and signature required on reverse side.

DATE ISSUED	25-Jun-12
PAGE 1 OF _____	

BID NUMBER Bid # 25	BID CLOSING DATE AND HOUR July 9, 2012 @ 10:00AM	REQUIRED DELIVERY DATE Days after award of Purchase Order
-------------------------------	--	--

TERMS:	DATE OF DELIVERY:
--------	-------------------

Item	Quantity	Unit of issue	DESCRIPTION	Unit Price	Total
			<p>Pittsburg County wishes to advertise for the following:</p> <p>One (1) or more new Motor Graders Lease with option to purchase with financing included</p> <p>See specifications attached</p>		

TERMS AND CONDITIONS

1. Sealed bids will be opened in the Commissioner's Conference Room, Pittsburg County Courthouse, McAlester, Oklahoma, at the time and date shown on the invitation to bid form.
2. Late bids will not be considered. Bids must be received in sealed envelopes (one to an envelope) with bid number and closing date written on the outside of the envelope.
3. Unit prices will be guaranteed correct by the bidder.
4. Firm prices will be F.O.B. destination.
5. Purchases by Pittsburg County, Oklahoma, are not subject to state or federal taxes.
6. This bid is submitted as a legal offer and any bid when accepted by the County constitutes a firm contract.
7. Oklahoma laws require each bidder submitting a bid to a county for goods or services to furnish a notarized sworn statement of non-collusion. A form is supplied below.
8. Bids will be firm until Delivered

(DATE)

AFFIDAVIT: I, the undersigned, of lawful age, being first duly sworn on oath say that he (she) is the agent authorized by the bidder to submit the above bid. Affiant further states that the bidder has not been a party to any collusion among bidders in restraint of freedom of competition by agreement to bid at a fixed price or to refrain from bidding; or with any state official or employee as to quantity; quality or price in the prospective contract or any other terms of said prospective contract; or in any discussions between bidders and any state official concerning exchange of money or other thing of value for special consideration in the letting of a contract; that the bidder/contractor has not paid, given or donated or agreed to pay, give or donate to any officer or employee of the State of Oklahoma (or other entity) any money or other thing of value, either directly or indirectly in the procuring of the award of a contract pursuant to this bid.

Subscribed and sworn before this _____ day
of _____ 2011 _____ (seal)

Firm: _____

My commission expires _____ Signed by: _____ Title: _____

(MANUAL SIGNATURE OF UNDERSIGNED)

_____ Address: _____ Phone: _____

NOTARY PUBLIC (CLERK OR JUDGE)

City: _____ State _____

Zip _____

NOTE: Other terms and conditions can be added at the discretion of the county officers.

RESOLUTION
To
Advertise

The Board of County Commissioners, Pittsburg County, met in regular session on Monday, June 25, 2012.

WHEREAS, Pittsburg County wishes to advertise for the following:

One (1) or more new Motor Graders, Lease with option to
Purchase with financing included

A bid package containing complete specifications and an "Invitation to Bid" are available at the Pittsburg County Clerk's Office, 115 E. Carl Albert Pkwy, Room 103, McAlester, Oklahoma 74501 or online at pittsburg.okcounties.org.


WHEREAS, each competitive bid submitted to the County must be accompanied with an affidavit for filing with the competitive bid form as required by 61 O.S. § 138.

THEREFORE, sealed bids will be received and filed with the County Clerk and opened by the Board of County Commissioners on Monday, July 9, 2012 at 10:00 a.m. in the County Commissioners Conference Room, Pittsburg County Courthouse, 115 E. Carl Albert Pkwy, McAlester, OK. Contract will be awarded to the lowest or best bidder. The Board of County Commissioners reserves the right to reject any and all bids and re-advertise.


BOARD OF COUNTY COMMISSIONERS
PITTSBURG COUNTY, OKLAHOMA



GENE ROGERS, Chairman




KEVIN SMITH, Member



RONNIE YOUNG, Vice-Chairman



ATTEST:



JANICE BARKER, County Clerk

**MOTOR GRADER SPECIFICATIONS
165 VARIABLE HORSEPOWER, ARTICULATED, 4 WHEEL DRIVE**

THE FOLLOWING SPECIFICATIONS ARE INTENDED TO PROVIDE FOR THE ACQUISITION OF ONE OR MORE MOTORGRADERS FOR PITTSBURG COUNTY VIA FULL WARRANTY LEASE ONLY. WHILE THE PROPOSED SPECIFICATIONS ARE CONSIDERED MINIMUM, PITTSBURG COUNTY RESERVES THE RIGHT TO ACCEPT OR REJECT ANY AND ALL BIDS, WAIVE MINOR IRREGULARITIES IN THE BIDS AND TO AWARD THIS BID IN THE BEST INTEREST OF PITTSBURG COUNTY. AWARD CRITERIA WILL INCLUDE CONFORMITY WITH THE SPECIFICATIONS, BID PRICE, FULL WARRANTY LEASE CRITERIA WITH FINANCING INCLUDED, DEALER PRODUCT SUPPORT CAPABILITY, PAST DEALER PERFORMANCE, MACHINE PERFORMANCE AND UNIT RESALE VALUE.

MINIMUM SPECIFICATIONS FOR MOTOR GRADERS:

GENERAL:

This machine shall be a new, currently advertised standard Production motor grader, serviced and ready for use with a full fuel tank.

Quality Standard Heat and Air Conditioner System

Head lights and directional light

Warning lights – roof mounted

WEIGHT:

Basic operating weight shall not be less than 35,300 lbs. Weight includes base machine, lubricants, coolants, full Fuel tank, operator, and attachments named in these specifications.

Front Counter Weight

ENGINE:

Ripper Assembly rear mounted with shanks and points

Engine shall be a six-cylinder, four stroke diesel

Engine shall develop a rated net flywheel power of at least 165 HP at an engine speed of no more than 1900 rpm.

Torque rise shall not be less than 30%

Fuel tank capacity shall be at least 90 US gallons

Engine enclosures, lockable

Air cleaner, dry element style with indicator

Variable horsepower shall be available to increase engine Power up to at least 180hp in the higher gear ranges for more productivity

TRANSMISSION:

Transmission shall be designed and built by the machine manufacturer

Transmission shall be a direct drive power shift or Torque convertor with heavy duty guard on bottom of transmission.

There shall be five working gears between 0-10 MPH

Transmission control shall be a single lever that controls over speed protection to prevent damage from premature downshifting.

Transmission removal shall be accomplished without removing the engine.

DIFFERENTIAL FINAL DRIVES/TANDEMS:

Operator controlled, multi-disc differential lock/unlock shall be provided.

Final drive shall be a planetary design.

Distance between center of tandem wheels shall not be less than 60 inches.

BRAKES:

Individual service brakes located at each of four tandem wheels.

Service brakes shall be multi-disc, oil-cooled, sealed and adjustment-free.

Service brake reserve system for dead engine braking shall be a dual type to allow braking in the event of a partial system failure.

Parking brake shall be a multi-disc, oil-cooled, spring-applied, sealed, and adjustment-free.

Engaged parking brake shall neutralize transmission.

AXLES/TIRES:

All standard tires shall be new, 14.00-24 12 PR Radial tubeless grader type with traction tread.

Wheel spindle shall rotate inside sealed compartment with lightweight Oil for lubrication of the bearings.

Front axle oscillation shall be no less than 32 degrees.

STEERING:

Front wheels steering angle shall be no less than 50 degrees, left or right.

Large steering stops located at each wheel and steering cylinder relief valve helping to prevent steering system damage.

Maximum front wheel lean shall be no less than 18 degrees Left or right.

Joystick control preferred for ease of operation, but not mandatory.

FRAME AND ARTICULATION JOINT:

Front frame shall be of flanged single box construction

The lower articulating joint shall have shim-adjustable tapered roller bearings for long life.

The articulation joint shall have a remote-mounted lube point for easy access.

Articulating joint shall have a mechanical locking device to prevent frame articulation while servicing or transporting machine.

MOLDBOARD:

The moldboard shall be at least 14 ft. long, 24" wide and 7/8" thick

Moldboard shall be constructed of a wear-resistant, high carbon steel

Moldboard shall be a maximum back slope angle of 90 degrees to both sides.

Moldboard shall have a hydraulic tip control through a range of 40 degrees forward and 5 degrees aft.

CIRCLE AND DRAWBAR:

The circle shall be supported by the drawbar with at least six support shoes providing vertical and horizontal adjustments.

Circle diameter shall be no less than 60 inches.

The teeth surface shall be hardened on the front 120 degrees of circle.

Blade and side shaft cylinders shall have replaceable wear inserts in the ball sockets.

Circle drive slip clutch shall be provided to reduce horizontal impact damage to moldboard.

WARRANTY:

Full machine warranty including mileage with exception of standard wear items.

GUARANTEED DELIVERY DATE:

PAYMENT MUST BE BID MONTHLY AND RENEWED EACH FISCAL YEAR.

LEASE MUST HAVE A TWO (2) SUCCESSIVE OPTIONS TO RENEW WITH ONE (1) ADDITIONAL OPTION TO RENEW FOR A TIME PERIOD OF _____ MONTHS TO EQUAL THIRTY-SIX (36) MONTHS.